



Trinity Innovations GeoTone Colored MDF Collection

Vibrant Color Through and Through



Design-rich elements that can be combined
to create stunning architectural statements




www.trinityinnovations.net

Trinity Innovations GeoTone Colored MDF Collection

Explore the Possibilities!


The GeoTone Collection embraces the natural beauty of earth tones for intrinsic perspectives. The coloring technology purposely leaves a few wood fibers without dye to accentuate the natural organic look.




BLACK




GRAY




BERRY



ROYAL



CURRY



TERRA

GEOTONE PHYSICAL PROPERTIES

Density	lbs/ft3	48
IB	psi	72-94
MOR	psi	4060-4930
MOE	psi	406-493K
MOH (Face Hardness)	lbs-Janka	n/a
Thickness Swell	%	9-15
Screw Holding Face	lbs	225-270
Screw Holding Edge	lbs	155-180
Lineal Expansion	%	0.25
Moisture Content	%	4-11
Fire Resistance		Class C
Fire Rated (ASTM E84)	10 min.	Class A
Formaldehyde		NAF
		Grey is CARB2

**APPLICATIONS INCLUDE CABINETRY,
FURNITURE, MILLWORK, SIGNAGE
AND LETTERING, STORE FIXTURES,
SHELVING, FLOORING AND CARVED
WALL/CEILING PANELS, AND MORE.**

Photos courtesy Sonae Indústria

GEOTONE AVAILABLE SIZES

Thickness	Color								
	Black		Black FR		Berry	Royal	Terra	Curry	Grey
	4x8	7x9	4x8	7x9	7x9	7x9	7x9	7x9	7x9
10mm	•	•	•	•	•	•	•	•	•
16mm	•	•	•	•	•	•	•	•	•
19mm	•	•	•	•	•	•	•	•	•
25mm		•		•	•	•	•	•	•

- All products are available with our UV or UV Plus clear coating
- Some items may be subject to minimum
- Color pictures may be slightly different than actual samples
- Physical properties are listed for informational purposes and have been supplied by the manufacturing company. Trinity Innovations takes no responsibility for the accuracy of this information.



KEY FEATURES OF GEOTONE COLORED MDF COLLECTION

- Color pigments are non-toxic and provide a consistent color throughout the panel
- Homogeneous density allows superior machinability and strength
- Solid color allows expanded 3D applications without the need for laminates or edge banding
- Colors and other materials can be combined to further expand design possibilities.
- FSC® Certification available
- Black is available with Class A Fire Rating (ASTM E84)
- Available as No Added Formaldehyde (NAF) and certified with CARB NAF Exempt Status



The mark of
responsible forestry

**For additional technical
details and instructions visit:
www.trinityinnovations.net
or call 916.258.3212**